

Features

****NEW** HAY-LDVR & HAY-LDVR-F**

Powder Coated Steel Construction

Mounting holes to mount the unit securely by its base

Vented both sides for improved airflow

Anti drill radial lock for added security

Easy cable access at rear, eg BNCs, IEC plugs and data cables

VDC, LDVR1, LDVR1-F have added front vent for HDD ventilation

LDVR1-F 1 x 12v fans expelling hot air from the cabinet @ 35CFM includes 12v PSU

LDVR-F 2 X 12v fans expelling hot air from the cabinet @ 70CFM includes 12v PSU

HAY-LDVR1 & LDVR1-F



HAY-V1100-200



THE NEW LDVR RANGE REPLACES THE HAY-LDVE, HAY-LDVR2 & HAYLDVR2-F



HAY-LDVR & HAY-LDVR-F

		DEPTH	WIDTH	HEIGHT	WEIGHT
HAY-LDVR	External	540mm	510mm	124mm	7.9kgs
	Internal	510mm	506mm	103mm	7.9kgs
HAY-LDVR-F	External	540mm	510mm	124mm	7.9kgs
	Internal	510mm	478mm	103mm	7.9kgs
HAY-LDVR1	External	445mm	404mm	120mm	6.0kgs
	Internal	400mm	354mm	91mm	6.0kgs
HAY-LDVR1-F	External	445mm	404mm	120mm	6.3kgs
	Internal	400mm	354mm	91mm	6.3kgs
HAY-VI100-200	External	450mm	260mm	238mm	6.2kgs
	Internal	428mm	244mm	233mm	6.2kgs