

ARU

ANSI Strikes

Range: CDVI UK®

Reversible

The ARU series of ANSI strikes offer fail-secure or fail-safe in one unit. Suitable for wooden or metal doors, these strikes are robust with a stainless steel jaw for added strength.

The design and high resistance to vandalism make it suitable to secure residential as well as industrial sites.

With monitoring available as an option and supplied complete with long and short faceplate, and full fixing kit for metal doors, the ARU series is truly a universal strike.



Commercial



Industrial



Public
Buildings



Multi-tenant
occupancy



Residential



ARU-M
Monitored version
Short faceplate



ARU
Non-monitored version
Long faceplate

Technical specifications

- **Dimensions (L x W x D):**
 - Lock body (incl. lip) 86 x 38 x 25mm
 - Short faceplate 124 x 32 x 2mm
 - Long faceplate 165 x 32 x 2mm
- **High quality stainless steel faceplates**
- **Operating temperature:**
 - 25°C to +70°C
- **Operating voltage:**
 - 12Vdc
- **Operating current:**
 - 250mA nominal

Key feature

- **ANSI Style**
- **Stainless steel jaw & faceplates**
- **Reversible - fail secure/fail safe**
- **Long & short faceplate included**
- **Monitored option**

Product Codes

ARU
ARU-M

ANSI STRIKE
ANSI STRIKE, MONITORED