

Upgraded image quality



SCB-2004

Premium Resolution Camera

- High resolution of 700TV lines
- Min. Illumination 0.1Lux color (F1.2, 50IRE)
- Day & Night (Electrical) SSNRIII, Defog
- Coax : Pelco-C (Coaxitron), Dual power




The SCB-2004 is a discreet general purpose analog box camera suitable for a wide range of applications. It incorporates the 6th generation Winner engine from Samsung Techwin that features premium level resolution at 700TV lines in sharp mode and other core functionalities such as SSNRIII, software day & night, and defog. It provides clear images under challenging environments, the SCB-2004 would be a perfect solution for who is looking for a cost effective high quality video surveillance camera.



Dimensions

Unit : mm (inch)



Accessory (Optional)



Specifications

	SCB-2004N	SCB-2004ND	SCB-2004P	SCB-2004PD
VIDEO				
Imaging Device	1/3" Super HAD CCD II			
Total Pixels	1,020(H) x 508(V)		1,020(H) x 596(V)	
Effective Pixels	976(H) x 494(V)		976(H) x 582(V)	
Scanning System	2 : 1 Interlace			
Synchronization	Internal / Line lock	Internal	Internal / Line lock	Internal
Frequency	H : 15.734KHz / V : 59.94Hz		H : 15.625KHz / V : 50Hz	
Horizontal Resolution	700TV lines (ER mode)			
Min. Illumination	0.1Lux@F1.2 (50IRE), 0.0002Lux (Sens-up, 512x)			
S / N Ratio	52dB (AGC off, Weight on)			
Video Output	CVBS : 1.0 Vp-p / 75Ω composite			
LENS				
Lens Type	Manual / Auto iris (DC)			
Mount Type	C / CS			
OPERATIONAL				
On Screen Display	English, Japanese, Spanish, French, Portuguese, Korean		English, French, German, Spanish, Italian, Chinese, Russian, Polish, Czech, Romanian, Serbian, Swedish, Danish, Turkish, Portuguese	
Camera Title	Off / On (Displayed 15 characters)			
Day & Night	Auto (Electrical) / Color / B/W			
Backlight Compensation	Off / BLC / HLC			
Contrast Enhancement	SSDR (Off / On)			
Digital Noise Reduction	SSNRIII (Off / On)			
Defog	Off / Auto / Manual			
Motion Detection	Off / On			
Privacy Masking	Off / On (8 programmable zones)			
Sens-up (Frame Integration)	2x ~ 512x			
Gain Control	Off / Low / Middle / High			
White Balance	ATW / Outdoor / Indoor / Manual / AWC (1,800°K ~ 10,500°K)			
Electronic Shutter Speed	1/60 ~ 1/120,000sec		1/50 ~ 1/120,000sec	
Reverse	H-Rev (Off / On)			
Communication	Coaxial control (SPC-300 compatible)			
Protocol	Coax : Pelco-C (Coaxitron)			
ENVIRONMENTAL				
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH			
ELECTRICAL				
Input Voltage / Current	Dual (24V AC & 12V DC ±10%)	12V DC ±10%	Dual (24V AC & 12V DC ±10%)	12V DC ±10%
Power Consumption	Max. 2.2W	Max. 1.3W	Max. 2.2W	Max. 1.3W
MECHANICAL				
Color / Material	Ivory / Plastic			
Dimensions (WxHxD)	70.0 x 47.3 x 99.7mm (2.76" x 1.86" x 3.93")			
Weight	120g (0.26 lb)	100g (0.22 lb)	120g (0.26 lb)	100g (0.22 lb)



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

Design and specifications are subject to change without notice.

■ DISTRIBUTED BY

SAMSUNG TECHWIN CO., LTD. 701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-400
Tel : +82-70-7147-8741~8749, 8752~8760 Fax : +82-31-8018-3745 www.samsungsecurity.com www.samsungcctv.com

SAMSUNG TECHWIN AMERICA INC.
100 Challenger Rd. Suite 700 Ridgely, NJ 07660
Toll Free : +1-877-213-1222 Direct : +1-201-325-6920
Fax : +1-201-373-0124

SAMSUNG TECHWIN EUROPE LTD.
2st floor No5, The Height, Brookland, Weybridge, Surrey, U.K.
KT13 0NY
Tel : +44-1932-82-6700 Fax : +44 1932 82 6701

SHANGHAI SAMSUNG TECHWIN CO., LTD.
32F, Bldg B, International Business Center,
No. 391 Guiping Rd., Shanghai, China, 200233
Tel : +86-21-5427-1155 Fax : +86-21-5423-5122



SAMSUNG TECHWIN