



EXTERNAL MAGNETIC LOCK (600LB)

MAGNETIC LOCK

IP66 external range of maglocks and brackets from a market leader in access control.



EXML600-GATE



SPECIFICATION

EXML600-GATE

- Stainless steel housing
- 280kg (600lb) holding force
- Dual voltage 12/24 VDC @ 500/250mA
- Comes complete with 1 metre cable
- Built in surge protection
- Surface mount
- Fail safe operation (power to lock)
- +/- 15% voltage tolerance
- -10° to +50° operating temperature
- Push off release pin on armature
- Monitored
- Voltage free relay contacts

FEATURES

EXML600-GATE

- External magnet IP66
- Weatherproof
- Dual voltage 12V/24V
- Side or face fixing
- Armature comes with fixing kit

Suitable Brackets/Housings:

- BKEX600ZL (ZL bracket)

OTHER PRODUCTS

WP66-G-CB-PTO



KPX75



RAINSHIELD



TRAN01-REC01



DIMENSIONS

EXML600-GATE

- 220x46x26 (mm) Maglock
- 200x44x20 (mm) Armature
- 2.64kg Boxed
- 1.55kg Unboxed

CONTENTS

EXML600-GATE

- External magnet
- Armature plate
- EX600GB fixing kit
- Instructions
- Armature fixing template



Manufactured by a BSIA Member