


TECHNICAL DATA SHEET

ZD49IR

INTUS Night Vision Camera with 4-9mm DC AI VF Lens, Soffit/Wall Mount



KEY FEATURES

- 1/3" Sony Super HAD CCD
- Ultra High Resolution, 560 TVL
- Impact Resistant Housing
- Sunshield and Heater
- Mechanical IR Cut-Filter
- Digital Noise Reduction (DNR)
- Built-in 42 IR LEDs with CDS Sensor
- Up to 30 Meters Illumination Range*
- Selectable Gain Control
- Selectable White Balance
- O.S.D. Menu
- Motion Detection
- Privacy Function
- External Control Rings for Easy Focus & Distance Adjustment
- Soffit / Wall Mountable Bracket with Base
- IP66 Rated
- Dual Voltage

* Important Note - The illumination range assumes ideal conditions

OPTIONAL ACCESSORIES

CCTV Power Supply In-Line 12V DC 3.5A Regulated Switch Mode Power Supply Unit with Fixing Mount.

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	ZD49IR
Image Sensor	1/3" Sony Super HAD CCD
Horizontal Resolution	560 TVL
Sensitivity (F1.2)	0.3 Lux (Col) 0.01 Lux (Mono) 0.002 Lux (Sens-Up ON x128)
Lens	4-9mm DC AI Varifocal
Effective Pixels (H x V)	752 x 582
Electronic Shutter Speed	1/50~1/120,000 Seconds
Scanning System	2:1 Interlace
Synchronisation	INT/LL Selectable
Frequency	Horizontal: 15.625KHz Vertical: 50.00Hz
Video Output	1.0Vp-p~75 Ohm
S/N Ratio	>50dB (AGC Off)
Colour	On/Auto Selectable
O.S.D.	Yes Built-In
Gain Control	LOW / HIGH / OFF Selectable
White Balance	ATW / AWB / MANUAL (1800°K~10500°K)
Back Light Compensation	LOW / MIDDLE / HIGH / OFF
DNR	ON / OFF (4 Levels)
Sharpness	ON / OFF (Level Adjustment)
Privacy Function	ON / OFF (4 Zones)
Motion Detection	ON / OFF (4 Zones)
D.I.S.	ON / OFF
Iris Control	DC / VIDEO
IP Rating	IP66
IR Illumination Range	30 Meters
Operating Conditions	Temperature: -20°C ~ +50°C, Humidity: 30 ~ 90% RH
Power Supply	DC 12V / AC 24V
Power Consumption	CDS ON: 1A Max
Dimensions (W x H x D)	88 x 115 x 245 mm
Weight	1.6 Kg
* Important Note - The illumination range assumes ideal conditions	

Features and specification are subject to change for further improvement without any notice.