

Veritas R8 Plus

Control Panel with Remote Keypad

Already renowned for its reliability, the Veritas R8 Plus has been upgraded with a host of new features. Installation and servicing are now even quicker. Operation is easier and more intuitive. Programming has been both simplified and extended. Make the right choice - the Veritas R8 Plus.

Outstanding Features



- 8 Fully Programmable Zones Plus Tamper
- Upload/Download Compatible
- 8 Channel Communicator Interface with Line Monitor
- EOL or Normally Closed Zone Operation
- 4 Programmable Part Set Suites
- Accepts Up To 6 Remote Keypads (LED or LCD)
- 8 Programmable Access Codes
- EN 50131 Grade 2
- 250 Event Log (Time/Date Stamped)
- 1.2mm Steel Enclosure Also Available



Also Accepts the Veritas Excel LCD Remote Keypad
Use as an extra keypad or as an engineer's programmer

Texecom
Designed to Perform

Veritas R8 Plus



8 Fully Programmable Zones Plus Tamper

The Veritas R8 Plus features 8 fully programmable zones plus an additional global system tamper. Each zone operates in any of the 8 different zone types ensuring exceptional system flexibility.



8 Channel Communicator Interface with Line Monitor

With an on-board 8 channel communicator interface, the Veritas R8 Plus can be used in conjunction with other signalling equipment as part of an ACPO compliant monitored alarm.



Universal Programming Platform

The Veritas R8 Plus utilises the same intuitive programming platform as the rest of the Veritas Series, ensuring instant product familiarity across the range.



Veritas R8 Endstation		
Current Consumption:	Quiescent current:	<50mA
	Alarm current:	<150mA
Power Supply:	Mains Supply Voltage Rating:	230VAC/115VAC ($\pm 10\%$)
	Max. Total Current Rating:	1Adc at 230VAC/115VAC ($\pm 5\%$)
	Ripple:	<5%
Dimensions:	282mm x 225mm x 80mm	

Veritas LED Remote Keypad		
Electrical:	Operating Voltage:	13.7Vdc nominal, 10.0Vdc min
	Current Consumption:	<70mA
Dimensions:	140mm x 105mm x 35mm	
Veritas LCD Remote Keypad		
Electrical:	Operating Voltage:	13.7Vdc nominal, 10.0Vdc min
	Current Consumption:	<70mA
Dimensions:	146mm x 116mm x 30mm	

Veritas Series



Veritas 8

Best selling stand alone control panel. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads.



Veritas R8 & Veritas R8 Plus

Best selling control panels with remote keypad. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads. Veritas R8 Plus also includes EOL wiring, communicator interface and accepts Veritas Excel LCD keypads.



Veritas 8 Compact

Slimline, discreet stand alone control panel. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads.



Veritas Excel

All the features of the Veritas R8 Plus including an LCD keypad for even easier programming and operation.

European Standards

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC).

Approved to BS EN 55022 Class B and BS EN 50130-4 : 1996.

PD 6662 & EN 50131 Grade 2 Environmental Class II.

The CE mark indicates that this product complies with the European requirements for safety, health, environmental and customer protection.

Texecom products are protected by UK and International patents, trademarks and registered design rights. UK Registered Design Numbers 1573433, 2041830, 2047440, 2055230 & 2089016.

Veritas is a trademark of Texecom Limited. ©2009 Texecom Ltd. (LIT-0076)



Certificate Number: FM 35285



A20090303